



32 bar -20/100°C		SUCTION ACCUMULATOR ACUMULADORES DE ASPIRACIÓN										HFC		R410A	
	Kg	Model Modelo	Code Código	Vol (L)	Conex.	Ø mm	B mm	H mm	E mm	Safety	Evap. Temp. Evap. (°C)	Recommended capacities			
												R 134 A		R 404 A / R 507 R410A	
												Máx	Mín	Máx	Mín
CAT. II	18	BT-180-A	12012	18	2 1/8"	219	225	660	114	3/8" NPT	-7	112	18,7	202	27,9
												-28.9	44	11,9	87,7
CAT. III	35	BT-360-A	12013	36	2 5/8"	323	350	637	170	3/8" NPT	-7	324	45,4	307,2	43,4
												-28.9	141	33,2	124,7
	36	BT-360-B	27003	36	3 1/8"	323	350	637	170	3/8" NPT	-7	324	45,4	307,2	43,4
												-28.9	141	33,2	124,7
	45	BT-500-A	27004	50	3 1/8"	323	350	809	170	3/8" NPT	-7	257	88,2	502,7	112,8
-28.9												105	58,6	200,7	115,2
58	BT-700-A	27005	70	3 5/8"	323	350	1065	170	3/8" NPT	-7	258	88,4	502,7	112,6	
											-28.9	105,5	59	200,6	115,2
CAT. IV	96	BT-1150-A	27006	115	4 1/8"	508	510	845	280	3/8" NPT	-7	259,5	88,7	502,6	112,3
												-28.9	107,2	59,7	200,3

VALID FOR ALL THE REFRIGERANTS HFC: R22, R134a, R404A, R507,ETC

VÁLIDO PARA TODOS LOS REFRIGERANTES HFC: R22, R134a, R404A, R507,ETC

ORDER / PEDIDO



TO INCLUDE THE SAFETY VALVE YOU MUST INDICATE IN YOUR ORDER:
PARA INCLUIR LA VÁL. SEGURIDAD, INDICAR EN EL PEDIDO:

MODEL / V.SG

EXAMPLE: BT-500-A / V.SG

ALL THE MODELS ARE PAINTED IN BLACK
TODOS LOS MODELOS SON PINTADOS EN NEGRO

