

PS07

Stainless steel isolated pressure sensor from 0 to 0.7 MPa

Description

PS07 is a high output amplified pressure transducer. It's particularly suited for use in the harsh automotive environment and for measurement of liquid or gas pressure even for difficult media such as contaminated water, steam, and mildly corrosive fluids.

The transducer pressure cavity is machined from a solid piece of 17-4 PH stainless steel.

Main Features

- Compatible with most fluids in automotive environment
- Fast response time
- Excellent durability

Benefits

- Small size
- High output
- High reliability
- Cost effective solution



Typical Applications

Measurement of fuel and oil pressure


PS07

Stainless steel isolated pressure sensor from 0 to 0.7 MPa

Technical Characteristics

Power supply	5 V
Supply current.....	< 10 mA
Null offset.....	0.5 V
Full scale output (@ Nominal Pressure)...	4.5 V
Pressure range	0 to 0.7 MPa
Operating temperature range	-20 to 85 °C
Compensated temperature range.....	0 to 55 °C
Accuracy (@ 25 °C).....	< 1 % f.s.o.
Span thermal error (@ 0 to 55 °C).....	< ±2 % f.s.o.
Burst Pressure	5 x Nominal Pressure
Vibrations range tested	
@ 0 Hz to 1000 Hz	(approx.) 10 g
Weight (approx.)	30 g

Dimensions



Note: this sensor PS07 must be mounted and installed with the Teflon

For further information, please contact:

MAGNETI MARELLI Motorsport
 Viale Aldo Borletti, 61/63
 20011 Corbetta (Milano) Italy

Tel. +39 02 972 27 478
 Fax +39 02 972 27 570
 sales@magnetimarelli.com
 http://www.magnetimarelli.com

November 2007
 rel. 03
 page 2 of 2

PS07-083813194700